

FALL ARRESTER - RANGER SAFETY (SRL) WITH ENERGY ABSORBER



CABLE
TYPE

- ❑ CE; EN360:2002 Certification
 - ❑ Reinforced Nylon Housing
 - ❑ 5mm Galvanized Wire Rope Cable; Wire Length: 6m*
 - ❑ Max user weight: 100kg / 220lbs; Max fall arrest force: 5.9KN
 - ❑ Energy Absorber integrated into lifeline
 - ❑ Extends & retracts to the movement of user automatically
- *Other lengths available upon request
- **NOTE: Max Service Angle (between webbing & vertical line of product)
MUST NOT Exceed 30° to minimise risk of swing fall



Tag Line
Supplied



BOTTOM

Auto-lock swivel carabiner

Energy Absorber



TOP



360°

Swivel top + Auto-lock carabiner attachment

CABLE TYPE SELF-RETRACTABLE LIFELINE

RETRACTABLE LIFELINE

RETRACTABLE LIFELINE



RL-06 **CE EN 360-2002**

- ◆ Housing Material: Reinforced nylon
- ◆ Wire rope diameter: 5mm
- ◆ Working length: 6M
- ◆ Max Arresting Force: 5.9kN
- ◆ Max Arresting Distance: 0.95m
- ◆ Capacity: 100kgs
- ◆ Locking after condition: 5kgs
- ◆ Static strength: 12kN with 3 mins
- ◆ Stainless Swivel Top
- ◆ Internal shock absorber system
- ◆ Quick lock carabiner
- ◆ Indicator Swivel Snaphook (Aluminium)



RL-15 **CE EN 360-2002**

- ◆ Housing Material: Aluminum
- ◆ Wire rope diameter: 5mm
- ◆ Working length: 15M
- ◆ Max Arresting Force: 3.2kN
- ◆ Max Arresting Distance: 1.45m
- ◆ Capacity: 100kgs
- ◆ Locking after condition: 5kgs
- ◆ Static strength: 12kN with 3 mins
- ◆ Stainless Swivel Top
- ◆ Internal shock absorber system
- ◆ Quick lock carabiner
- ◆ Indicator Swivel Snaphook (Aluminium)



RL-10 **CE EN 360-2002**

- ◆ Housing Material: Reinforced nylon
- ◆ Wire rope diameter: 5mm
- ◆ Working length: 10M
- ◆ Max Arresting Force: 3.5kN
- ◆ Max Arresting Distance: 1.14m
- ◆ Capacity: 100kgs
- ◆ Locking after condition: 5kgs
- ◆ Static strength: 12kN with 3 mins
- ◆ Stainless Swivel Top
- ◆ Internal shock absorber system
- ◆ Quick lock carabiner
- ◆ Indicator Swivel Snaphook (Aluminium)



RL-20 **CE EN 360-2002**

- ◆ Housing Material: Aluminum
- ◆ Wire rope diameter: 5mm
- ◆ Working length: 20M
- ◆ Max Arresting Force: 3.2kN
- ◆ Max Arresting Distance: 1.54m
- ◆ Capacity: 100kgs
- ◆ Locking after condition: 5kgs
- ◆ Static strength: 12kN with 3 mins
- ◆ Stainless Swivel Top
- ◆ Internal shock absorber system
- ◆ Quick lock carabiner
- ◆ Indicator Swivel Snaphook (Aluminium)



WEBBING TYPE SELF-RETRACTABLE LIFELINE

WRL/WARL-1.5/02/03 CE EN 360-2002



- ◆ Housing Material: High-Strength ABS
- ◆ Webbing: 20mm Dyneema
- ◆ Working length: 1.5M/2M/3M
- ◆ Max Arresting Force: 5.1kN/5.3kN/2.8kN
- ◆ Max Arresting Distance: 0.88M/0.98M/1.91M
- ◆ Capacity: 100kgs
- ◆ Locking after condition: 5kgs
- ◆ Static strength: 12kN with 3 mins
- ◆ Stainless Swivel Top
- ◆ Internal shock absorber system
- ◆ Quick lock carabiner
- ◆ Indicator Swivel Snaphook (Aluminium)
- ◆ Sewn-in Fall Indicator



SRL-2D CE EN 360-2002

- ◆ Housing Material: PA6 Enhancement
- ◆ Webbing: 17mm Dyneema
- ◆ Working length: 1.8M/2M
- ◆ Max Arresting Force: <6kN
- ◆ Max Arresting Distance: <2M
- ◆ Capacity: 100kgs
- ◆ Locking after condition: 5kgs
- ◆ Static strength: 12kN with 3 mins
- ◆ Stainless Swivel Top
- ◆ Internal shock absorber system
- ◆ Triple lock Aluminum carabiner
- ◆ Indicator Swivel Snaphook (Aluminium)
- ◆ Sewn-in Fall Indicator

WRL-06/WARL-06 CE EN 360-2002



- ◆ Housing Material: Reinforced nylon
- ◆ Webbing: 20mm Dyneema
- ◆ Working length: 6M
- ◆ Max Arresting Force: 3.1kN
- ◆ Max Arresting Distance: 1.45m
- ◆ Capacity: 100kgs
- ◆ Locking after condition: 5kgs
- ◆ Static strength: 12kN with 3 mins
- ◆ Stainless Swivel Top
- ◆ Internal shock absorber system
- ◆ Quick lock carabiner
- ◆ Indicator Swivel Snaphook (Aluminium)



SRL-2DB CE EN 360-2002

- ◆ Housing Material: PA6 Enhancement
- ◆ Webbing: 17mm Dyneema
- ◆ Working length: 1.8M/2M
- ◆ Max Arresting Force: <6kN
- ◆ Max Arresting Distance: <2M
- ◆ Capacity: 100kgs
- ◆ Locking after condition: 5kgs
- ◆ Static strength: 12kN with 3 mins
- ◆ Stainless Swivel Top
- ◆ Internal shock absorber system
- ◆ Triple lock Aluminum carabiner
- ◆ Indicator Snaphook (Aluminium)
- ◆ Sewn-in Fall Indicator

