

# FLAT WEBBING SLING



## Double Ply Flat Webbing

ART.NO.	W.L.L. (kg)	5:1&6:1 WIDTH (mm)	7:1&8:1 WIDTH (mm)	COLOR	WLL in kg at different modes				
					Straight lift	Basket lift	7°-45°	Choker hitch	45°-60°
TP-WS-201	1000	25	30	Violet	1000	2000	1400	800	1000
TP-WS-202	2000	50	60	Green	2000	4000	2800	1600	2000
TP-WS-203	3000	75	90	Yellow	3000	6000	4200	2400	3000
TP-WS-204	4000	100	120	Grey	4000	8000	5600	3200	4000
TP-WS-205	5000	125	150	Red	5000	10000	7000	4000	5000
TP-WS-206	6000	150	180	Brown	6000	12000	8400	4800	6000
TP-WS-208	8000	200	240	Blue	8000	16000	11200	6400	8000
TP-WS-210	10000	250	300	Orange	10000	20000	14000	8000	10000
TP-WS-212	12000	300	300	Orange	12000	24000	16800	9600	12000

## Four Ply Flat Webbing

ART.NO.	W.L.L. (kg)	5:1&6:1 WIDTH (mm)	7:1&8:1 WIDTH (mm)	COLOR	WLL in kg at different modes				
					Straight lift	Basket lift	7°-45°	Choker hitch	45°-60°
TP-WS-401	2000	25	30	Violet	2000	4000	2800	1600	2000
TP-WS-402	4000	50	60	Green	4000	8000	5600	3200	4000
TP-WS-403	6000	75	90	Yellow	6000	12000	8400	4800	6000
TP-WS-404	8000	100	120	Grey	8000	16000	11200	6400	8000
TP-WS-405	10000	125	150	Red	10000	20000	14000	8000	10000
TP-WS-406	12000	150	180	Brown	12000	24000	16800	9600	12000
TP-WS-408	16000	200	240	Blue	16000	32000	22400	12800	16000
TP-WS-410	20000	250	300	Orange	20000	40000	28000	16000	20000
TP-WS-412	24000	300	300	Orange	24000	48000	33600	19200	24000



- 100 Polyester
- Compliance to EN1492-1+ A1:2008
- CE & G.S. Certified
- Low Weight, easy handling
- Highly flexible & adaptable to given shapes
- UV-resistant
- Heat-resistant up to 100°C
- Water-resistance, prevent frost damage (down to -40°C)
- Soft sewn eyes ( Flat, Becket, Reverse eyes)
- Reinforced lifting eyes
- Low elongation