

ROUND SLING



ART.NO.	W.L.L. (kg)	WIDTH (mm)	COLOR	WLL in kg at different modes				
				Straight lift	Basket lift	7°-45°	Choker hitch	45°-60°
TP-RS-01	1000	45	Violet	1000	2000	1400	800	1000
TP-RS-02	2000	50	Green	2000	4000	2800	1600	2000
TP-RS-03	3000	60	Yellow	3000	6000	4200	2400	3000
TP-RS-04	4000	75	Grey	4000	8000	5600	3200	4000
TP-RS-05	5000	85	Red	5000	10000	7000	4000	5000
TP-RS-06	6000	90	Brown	6000	12000	8400	4800	6000
TP-RS-08	8000	105	Blue	8000	16000	11200	6400	8000
TP-RS-10	10000	115	Orange	10000	20000	14000	8000	10000
TP-RS-12	12000	120	Orange	12000	24000	16800	9600	12000
TP-RS-15	15000	130	Orange	15000	30000	21000	12000	15000
TP-RS-20	20000	130	Orange	20000	40000	28000	16000	20000
TP-RS-25	25000	175	Orange	25000	50000	35000	20000	25000
TP-RS-30	30000	175	Orange	30000	60000	42000	24000	30000
TP-RS-40	40000	220	Orange	40000	80000	56000	32000	40000
TP-RS-50	50000	220	Orange	50000	100000	70000	40000	50000

- Compliance to EN1492-2+ A1:2008
- CE & G.S. Certified
- Safety factor of 7:1
- High strength to weight ratio
- Wears evenly along the length
- Load bearing fiber protected from the load, giving greater resistance to wear

